




DRAWING





FEATURES

- Glass fibre reinforced plastic (PBT) fan casing and impeller.
- Brushless dc motor, impedance protected against running overload.
- Electrical connection via 2 leads UL1007 AWG24, 300mm long.
- Rated temperature range:
Ball bearing from -20°C to +70°C
Sleeve bearing from -10°C to +60°C
- Service life L10:
Ball bearing 70,000 hours at 40°C
40,000 hours at t max
Sleeve bearing 50,000 hours at 40°C
35,000 hours at t max
- Weight 70g.

Please refer to our terms of sales including our warranty and limited liabilities clauses.

AIR FLOW CURVES



Model	Diagram	Bearing #		Rated Voltage [V]	Input Power [W]	Speed [rpm]	Air Flow [m3/h]	Static Pressure [Pa]	Noise [dB(A)]	Approvals		
		S	B							UL	CUL	TUV
D08D04HW#A00	1	➔	➔	12	2.9	3,100	49	37	32.4	➔	➔	
D08D04MW#A00	2	➔	➔	12	1.9	2,550	40	24	27.0	➔	➔	
D08D05HW#A00	1	➔	➔	24	3.6	3,100	49	37	32.4	➔	➔	
D08D05MW#A00	2	➔	➔	24	3.1	2,550	40	24	27.0	➔	➔	

“#” : S= Sleeve, B= Ball