

Data sheet

Commercial Art.No.: R1.188.3630.0

Stand still monitor SNS 4074K-C DC 24V 9,9 HZ

Zero-speed monitor (Frequency range 0.1 - 9.9 Hz) with bypass-function, automatic-/ manual reset with reset-button monitoring, 4 safe semiconductor outputs, DC 24 V, pluggable push-ins

1011011010001010010101101
0100110110010110100101010
1010011011001110010100100
101101001010101010010100
1101010011011001011010010
10101010010101101010011

DIGITALIZATION IN PROGRESS

Commercial Art.No.	R1.188.3630.0
EAN	4049088101946
Order Unit	1

Certificates / Approvals



Image not found or type unknown



Technical data

General

Function display	12 LED, green/red
Creepage distances and clearances between the circuits	EN 60664-1
Protection degree according to DIN EN 60529 (housing)	IP40
Protection degree according to DIN EN 60529 (terminals)	IP20
Ambient temperature min.	-25 °C
Ambient temperature max.	55 °C
Permissible torque min.	0.5 Nm
Permissible torque max.	0.6 Nm
Tightening moment	0.6 Nm
Wire range cage clamp terminals	2 x 0,25mm ² - 1,5mm ²
Weight	0.16 kg
Standards	EN ISO 13849-1EN 62061; EN 62061
Suited for safety functions	Yes
With muting function	Yes
Feedback circuit	Yes
Start contact	Yes
Stop category acc. to IEC 60204	0
Rail mounting possible	Yes

Connection Data

Detachable clamps	Yes
Type of electric connection	Spring clamp connection

Output circuit

Enabling paths	solid state (plus), safe output
Signaling paths	solid state (plus), not safe

Rated switching voltage, enabling paths DC	30 V
Max. thermal current I_{th} , enabling paths	2 A
Max. total current I^2 of all current path	4 A ²
Short-circuit protection (NO), max. fuse insert	short-circuit proof
Outputs, signalling function, undelayed, with contact	2
Outputs, safe, undelayed, with contact	4

Control circuit

Nominal output voltage DC	24 V
Input current (safety circuit / reset circuit)	3 mA
max. peak current (safety circuit / reset circuit)	3.8 mA
Min. switch-on time	100 ms
Recovery time t_W	> 100 ms
max. resistivity, per channel	100 m
Evaluation inputs	2-channel

Supply circuit

Nominal voltage U_N	DC 24 V
Rated consumption DC	1.8 W
Electrical isolation supply circuit - control circuit	No
Min. rated DC voltage for controls	20.4 V
Max. rated DC voltage for controls	30 V

Dimensions

Depth	114 mm
Width	22.5 mm
Height	106.5 mm

Classification

ECLASS 8.1	27371811
ETIM 7.0	EC001448
ETIM 6.0	EC001448
ETIM 5.0	EC001448

Application

Model	Basic device
Suitable for monitoring of magnetic switches	No
Suitable for monitoring of proximity switches	Yes

Safety parameters

Category (ISO 13849-1)	4
PL (ISO 13849-1)	Level e
SIL _{CL} (IEC 62061)	3
PFD _d (Low demand mode)	2.2 E-5
PFH _d (High demand mode)	5 E-9 1/h
HFT	1
DC	96 %
MTTF _d	300 a

T _M	20 a
Proof test intervall (High demand mode)	20 a

Teile Nr. / Part No.
R1.188.1940.0
R1.188.1950.0
R1.188.1960.0
R1.188.1970.0
R1.188.1980.0
R1.188.1990.0
R1.188.2000.0
R1.188.2010.0
R1.188.2020.0
R1.188.2390.0
R1.188.2410.0
R1.188.2420.0
R1.188.2430.0
R1.188.2440.0
R1.188.2450.0
R1.188.3400.0
R1.188.3410.0
R1.188.3420.0
R1.188.3430.0
R1.188.3490.0
R1.188.3600.0

Teile Nr. / Part No.
R1.188.3610.0
R1.188.3630.0
R1.188.3650.0
R1.188.3670.0
R1.188.3730.0
R1.188.3820.0
R1.188.3850.0
R1.188.3860.0
R1.188.3900.0
R1.188.3920.0
R1.188.3940.0
R1.188.4000.0
R1.188.4010.0
R1.188.4030.0
R1.188.4130.0
R1.188.4140.0
R1.188.4150.0
R1.188.4160.0
R1.188.4210.0
R1.188.5000.0




Ⓓ

Ⓑ

Ⓒ

Ⓔ

Ⓕ



Weitere Angaben siehe KATALOG oder eKatalog.
Additional data see CATALOG or eCatalog.

www.wieland-electric.com
eshop.wieland-electric.com

ja/yes ☐ Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten. Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!															
Freitoleranz nach General tolerance				CAD-Zeichnung, keine manuellen Änderungen CAD-Drawing, no manual modifications allowed			1. Verwendung: First Use:		Blatt: Sheet:						
Ⓕ		09.08.19				Werkstoff/Material		2014		Tag/Date		Name		Zeichnung Nr./Drawing No. T R1.188.1940.0 01K	
Ⓔ		26.08.16						gezeichnet drawn		06.06.		Koetzner			
Ⓓ		22.04.16						geprüft checked							
Ⓒ		03.07.15		Datei/File:		036141_F01K.DCD				Ersatz für/Replacement for:					
Ⓑ		30.06.15				www.wieland-electric.com		Type		Benennung/Title Maßbildzeichnung/Dimension drawing Standardgehäuse u. -deckel, Baubreite 22,5mm, Federkraftklemme steckbar Standard housing and cover, overall width 22,5mm plug-in spring-clamp terminal					
Ⓓ		03.02.15													
Index		Datum/Blatt Date/Sheet													
Änderung/Revision															